

Package: DOIcreator (via r-universe)

May 12, 2026

Title Append DOIs to References in Word Documents

Version 0.1.0

Description DOIcreator is an R package that reads Word documents containing bibliographic references, searches for their corresponding DOIs via the CrossRef API, and appends the DOIs directly to the references. It supports parallel processing for faster retrieval and outputs a new Word document with numbered references including DOIs.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

Imports httr, jsonlite, officer

Suggests knitr, rmarkdown

VignetteBuilder knitr

Config/pak/sysreqs libfontconfig1-dev libfreetype6-dev libfribidi-dev libharfbuzz-dev libicu-dev libjpeg-dev libpng-dev libtiff-dev libwebp-dev libxml2-dev libssl-dev

Repository <https://umarhussain-git.r-universe.dev>

Date/Publication 2025-12-01 18:13:08 UTC

RemoteUrl <https://github.com/umarhussain-git/doicreator>

RemoteRef HEAD

RemoteSha 04b462dc5129c44464620493790d902067e713e2

Contents

add_doi	2
Index	3

`add_doi`*Add DOIs to References in a Word Document*

Description

This function reads a Word document containing bibliographic references, fetches their corresponding DOIs via the CrossRef API, and writes a new Word document with the DOIs appended to each reference.

Usage

```
add_doi(input_path, output_path, reference_lines = 50)
```

Arguments

<code>input_path</code>	Character. Path to the input Word document (.docx) containing references. Can be absolute (e.g., "C:/Users/.../references.docx") or relative (e.g., "./references.docx").
<code>output_path</code>	Character. Path where the output Word document with DOIs will be saved. If the file exists, it will be overwritten.
<code>reference_lines</code>	Numeric. Number of lines from the end of the document to treat as references. Default is 50. Only lines with more than 30 characters are processed.

Value

Character vector of references with appended DOIs. References that could not be matched return "NA".

Examples

```
## Not run:
# Basic usage: fetch DOIs for last 50 lines in a Word document
add_doi(
  input_path = "E:/references.docx",
  output_path = "E:/references_doi.docx",
  reference_lines = 50
)

# Notes:
# - input_path must exist and contain references.
# - output_path will be overwritten if it exists.
# - Some references may return DOI "NA" if not found on CrossRef.

## End(Not run)
```

Index

`add_doi`, [2](#)