

Package: contourforest (via r-universe)

May 22, 2026

Type Package

Title Contour-Enhanced Forest Plots for Meta-Analysis

Version 0.1.0

Description Provides functions to create contour-enhanced forest plots for continuous and binary outcomes in meta-analysis, including options for prediction intervals, customized colors, and study labeling. Based on 'metafor' and 'ggplot2'.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

Imports ggplot2, dplyr, metafor, stringr, grid

VignetteBuilder knitr

Suggests knitr, rmarkdown

Depends R (>= 4.0.0)

Config/pak/sysreqs libicu-dev

Repository <https://umarhussain-git.r-universe.dev>

Date/Publication 2025-12-18 07:06:03 UTC

RemoteUrl <https://github.com/umarhussain-git/contourforest>

RemoteRef HEAD

RemoteSha fd2c5c1709bdaafadc6e883f1db32b46d641b30f

Contents

bcg	2
dat1	2
forest_bin	3
forest_bin_subgroup	5
forest_cont	7
forest_cont_subgroup	10

Index**13**

bcg	<i>BCG Vaccine Trials Dataset</i>
-----	-----------------------------------

Description

This dataset contains summary data from 13 BCG vaccine studies, including the number of events in treatment and control groups, total sample sizes, and subgroup classification.

Usage

```
bcg()
```

Value

A data frame with 13 rows and 6 variables:

Study Character. Name and year of the study.

events_t Numeric. Number of events (e.g., TB cases) in the treatment (BCG) group.

n_t Numeric. Total number of participants in the treatment group.

events_c Numeric. Number of events in the control group.

n_c Numeric. Total number of participants in the control group.

subgroup Character. Type of study or subgroup classification ("random", "alternate", or "systematic").

dat1	<i>Hypothetical dataset: GAD-7 Anxiety Scores by Socioeconomic Status</i>
------	---

Description

GAD-7 scores (mean \pm SD) for high SES (control) vs low SES (treatment) groups across 6 studies.

Usage

```
dat1
```

Format

A data frame with 6 rows and 8 variables:

Study Study name or year

mean_c Mean GAD-7 score in high SES (control) group

sd_c Standard deviation of GAD-7 scores in high SES (control) group

n_c Sample size in high SES (control) group

mean_t Mean GAD-7 score in low SES (treatment) group

sd_t Standard deviation of GAD-7 scores in low SES (treatment) group

n_t Sample size in low SES (treatment) group

subgroup Geographical subgroup of the study (e.g., Asia, Europe)

Source

Hypothetical data

forest_bin

Contour-Enhanced Binary Outcome Forest Plot

Description

Generates a contour-enhanced forest plot for binary outcome data (e.g., odds ratios, risk ratios), with study-level effects, confidence intervals, pooled effect, prediction interval, and heterogeneity statistics.

Usage

```
forest_bin(
  dat,
  measure = "OR",
  method = "REML",
  xlab = "",
  title = NULL,
  model = "Random-effects",
  estimator = "REML",
  nc_col = "n_c",
  ne_col = "n_t",
  event_c_col = "events_c",
  event_t_col = "events_t",
  diamond.col = "red",
  study.col = "blue",
  CI.col = "blue",
  Pred.Inter.col = "black",
  square.size = 10,
  contour_fill = c("gray95", "gray80", "gray60", "gray40"),
```

```

text_size = 3.5,
xlim = c(-1.7, 3.5),
pred = TRUE,
xpos = list(EventsT = -0.9, EventsC = -0.3, Effect = 2.6, Weight = 3.1),
study_x = -1.8,
hetero_x = -1.7,
tlim = c(0, 2.3),
truncate_PI = FALSE,
contour_left_min = c(0, 0.5, 0.67, 0.83),
contour_left_max = c(0.5, 0.67, 0.83, 1),
contour_right_min = c(1, 1.2, 1.5, 2),
contour_right_max = c(1.2, 1.5, 2, 2.5)
)

```

Arguments

<code>dat</code>	Data frame containing study-level binary outcome data.
<code>measure</code>	Character. Effect measure ("OR" for odds ratio, "RR" for risk ratio, etc.).
<code>method</code>	Character. Method for meta-analysis heterogeneity estimation (default "REML").
<code>xlab</code>	Character. Label for the x-axis.
<code>title</code>	Character. Plot title. If NULL, a default title is generated.
<code>model</code>	Character. Meta-analysis model ("Random-effects" or "Fixed-effects").
<code>estimator</code>	Character. Estimator used in the meta-analysis (default "REML").
<code>nc_col</code>	Character. Column name for control group sample sizes.
<code>ne_col</code>	Character. Column name for treatment group sample sizes.
<code>event_c_col</code>	Character. Column name for number of events in control group.
<code>event_t_col</code>	Character. Column name for number of events in treatment group.
<code>diamond.col</code>	Color of the pooled effect polygon.
<code>study.col</code>	Color of the study-level effect points.
<code>CI.col</code>	Color of the study-level confidence interval lines.
<code>Pred.Inter.col</code>	Color of the prediction interval line.
<code>square.size</code>	Numeric. Maximum size of study-level effect squares.
<code>contour_fill</code>	Vector of colors for contour shading levels.
<code>text_size</code>	Numeric. Base size of plot text.
<code>xlim</code>	Numeric vector of length 2. Limits of the x-axis.
<code>pred</code>	Logical. Whether to show the prediction interval.
<code>xpos</code>	List of numeric positions for text labels (EventsT, EventsC, Effect, Weight).
<code>study_x</code>	Numeric. X-position for study names.
<code>hetero_x</code>	Numeric. X-position for heterogeneity text.
<code>tlim</code>	Numeric vector of length 2. Limits for truncating study confidence intervals.
<code>truncate_PI</code>	Logical. Whether to truncate the prediction interval to <code>tlim</code> .

contour_left_min
 Numeric vector. Minimum x-values for left-side contour shading.

contour_left_max
 Numeric vector. Maximum x-values for left-side contour shading.

contour_right_min
 Numeric vector. Minimum x-values for right-side contour shading.

contour_right_max
 Numeric vector. Maximum x-values for right-side contour shading.

Value

A ggplot2 object of the forest plot.

Examples

```
forest_bin(
  dat = bcg(),
  measure = "OR",
  xlab = "Odds Ratio",
  title = "BCG Vaccine Meta-analysis",
  tlim = c(0, 2.3),
  contour_left_min = c(0,0.3,0.5,0.7),
  contour_left_max = c(0.3,0.5,0.7,1),
  contour_right_min = c(1,1.2,1.5,1.8),
  contour_right_max = c(1.2,1.5,1.8,2.5)
)
```

forest_bin_subgroup *Subgroup Forest Plot for Binary Outcome Meta-analysis*

Description

Generates a contour-enhanced forest plot for binary outcome data, with optional subgroup analysis. This function calculates risk ratios (or other measures) and displays study-specific effect sizes, pooled subgroup effects, overall pooled effect, and heterogeneity statistics (I^2 , τ^2).

Usage

```
forest_bin_subgroup(
  dat,
  subgroup = NULL,
  measure = "RR",
  method = "REML",
  nc_col = "n_c",
  ne_col = "n_t",
  event_c_col = "events_c",
  event_t_col = "events_t",
  xlab = "Risk Ratio (RR)",
```

```

title = "Subgroup Forest Plot",
diamond.col = "red",
overall.col = "darkgreen",
study.col = "blue",
CI.col = "blue",
Pred.Inter.col = "black",
square.size = 8,
Pred.Int.size = 2,
xlim = c(-2, 3.5),
tlim = c(0, 2.3),
text_size = 3.5,
xpos = list(EventsT = -1, EventsC = -0.4, Effect = 2.5, Weight = 3.2),
study_x = -1.8,
val_x = 2.6,
contour_left_min = c(0, 0.5, 0.67, 0.83),
contour_left_max = c(0.5, 0.67, 0.83, 1),
contour_right_min = c(1, 1.2, 1.5, 2),
contour_right_max = c(1.2, 1.5, 2, 2.5),
pred = TRUE
)

```

Arguments

dat	A data frame containing study-level data. Must include columns for treatment and control events and sample sizes, and optionally a subgroup column.
subgroup	Column name in dat specifying subgroup membership (character or factor). Defaults to NULL (no subgroups).
measure	Effect measure to use. Default is "RR" (risk ratio).
method	Method for random-effects meta-analysis. Default is "REML".
nc_col	Character. Column name for control group sample sizes.
ne_col	Character. Column name for treatment group sample sizes.
event_c_col	Character. Column name for number of events in control group.
event_t_col	Character. Column name for number of events in treatment group.
xlab	Label for the x-axis. Default is "Risk Ratio (RR)".
title	Plot title. Default is "Subgroup Forest Plot".
diamond.col	Color for subgroup pooled effect diamonds. Default is "red".
overall.col	Color for overall pooled effect diamond. Default is "darkgreen".
study.col	Color for individual study points. Default is "blue".
CI.col	Color for study confidence interval bars. Default is "blue".
Pred.Inter.col	Color for prediction interval bars. Default is "black".
square.size	Maximum size of study points. Default is 8.
Pred.Int.size	Thickness of prediction interval line. Default is 2.
xlim	Numeric vector of length 2 giving x-axis limits. Default is c(-2, 3.5).

tlim	Numeric vector of length 2 for truncating study CIs. Default is c(0, 2.3).
text_size	Base text size for labels. Default is 3.5.
xpos	List of x-axis positions for EventsT, EventsC, Effect, and Weight labels. Default is list(EventsT=-1, EventsC=-0.4, Effect=2.5, Weight=3.2).
study_x	X position for study names. Default is -1.8.
val_x	X position for pooled effect labels. Default is 2.6.
contour_left_min	Numeric vector defining left contour minimum values. Default is c(0, 0.5, 0.67, 0.83).
contour_left_max	Numeric vector defining left contour maximum values. Default is c(0.5, 0.67, 0.83, 1).
contour_right_min	Numeric vector defining right contour minimum values. Default is c(1, 1.2, 1.5, 2).
contour_right_max	Numeric vector defining right contour maximum values. Default is c(1.2, 1.5, 2, 2.5).
pred	Logical indicating whether to show the prediction interval. Default is TRUE.

Value

A ggplot object representing the contour-enhanced subgroup forest plot.

Examples

```
# Load example dataset
data <- bcg()

# Generate subgroup forest plot
forest_bin_subgroup(
  dat = bcg(),
  tlim = c(0, 2.3),
  contour_left_min = c(0, 0.3, 0.5, 0.7),
  contour_left_max = c(0.3, 0.5, 0.7, 1),
  contour_right_min = c(1, 1.2, 1.5, 1.8),
  contour_right_max = c(1.2, 1.5, 1.8, 2.4)
)
```

forest_cont

Contour-enhanced Forest Plot for Continuous Outcomes

Description

Creates a forest plot for continuous outcomes (MD or SMD) with optional contour shading, prediction interval, and annotated study-level means, effect sizes, and weights.

Usage

```

forest_cont(
  dat,
  measure = "SMD",
  method = "REML",
  sort = c("effect", "none"),
  xlab = "",
  title = NULL,
  model = "Random-effects",
  estimator = "REML",
  m_c_col = "mean_c",
  sd_c_col = "sd_c",
  n_c_col = "n_c",
  m_t_col = "mean_t",
  sd_t_col = "sd_t",
  n_t_col = "n_t",
  diamond.col = "red",
  study.col = "blue",
  CI.col = "blue",
  Pred.Inter.col = "black",
  contour_left_min = c(-0.8, -0.5, -0.2, 0),
  contour_left_max = c(-0.5, -0.2, 0, 0.2),
  contour_right_min = c(0, 0.2, 0.5, 0.8),
  contour_right_max = c(0.2, 0.5, 0.8, 1),
  square.size = 10,
  contour_fill = c("gray95", "gray80", "gray60", "gray40"),
  text_size = 3.5,
  pred = TRUE,
  study_x = NULL,
  treatment_x = NULL,
  control_x = NULL,
  effect_x = NULL,
  weight_x = NULL,
  PredInt_x = NULL,
  xlim = NULL,
  hetero_x = -8
)

```

Arguments

dat	Data frame containing study-level data. Must include treatment and control means, SDs, sample sizes, and study labels.
measure	Effect size measure: "MD" (mean difference) or "SMD" (standardized mean difference). Default is "SMD".
method	Meta-analysis method for <code>rma()</code> (e.g., "REML"). Default is "REML".
sort	Logical. If TRUE, the studies will be sorted by effect size before plotting.
xlab	Label for the x-axis.

title	Plot title. If NULL, a default title including measure is used.
model	Model description for heterogeneity annotation. Default "Random-effects".
estimator	Estimator for heterogeneity. Default "REML".
m_c_col	Column name for control group means. Default "mean_c".
sd_c_col	Column name for control group SDs. Default "sd_c".
n_c_col	Column name for control group sample sizes. Default "n_c".
m_t_col	Column name for treatment group means. Default "mean_t".
sd_t_col	Column name for treatment group SDs. Default "sd_t".
n_t_col	Column name for treatment group sample sizes. Default "n_t".
diamond.col	Color for the pooled effect diamond. Default "red".
study.col	Color for study effect points. Default "blue".
CI.col	Color for study confidence intervals. Default "blue".
Pred.Inter.col	Color for prediction interval. Default "black".
contour_left_min	Numeric vector specifying the left-side minimum x-axis boundaries for contour shading bands (values less than the null effect).
contour_left_max	Numeric vector specifying the left-side maximum x-axis boundaries for contour shading bands (values less than or equal to the null effect).
contour_right_min	Numeric vector specifying the right-side minimum x-axis boundaries for contour shading bands (values greater than or equal to the null effect).
contour_right_max	Numeric vector specifying the right-side maximum x-axis boundaries for contour shading bands (values greater than the null effect).
square.size	Size of study points. Default 10.
contour_fill	Vector of four colors for contour shading. Default c("gray95", "gray80", "gray60", "gray40").
text_size	Size of annotated text. Default 3.5.
pred	Logical; whether to show prediction interval. Default TRUE.
study_x	X-position for study labels. Default computed automatically.
treatment_x	X-position for treatment means. Default computed automatically.
control_x	X-position for control means. Default computed automatically.
effect_x	X-position for effect sizes. Default computed automatically.
weight_x	X-position for weights. Default computed automatically.
PredInt_x	X-position for prediction interval label. Default computed automatically.
xlim	X-axis limits. Default computed automatically.
hetero_x	X-position for heterogeneity annotation. Default -8.

Value

A ggplot2 object representing the forest plot.

Examples

```
forest_cont(  
  dat1,  
  measure = "MD",  
  xlab = "Mean Difference",  
  study_x = -9,  
  sort = "effect",  
  hetero_x = -12,  
  treatment_x = -7,  
  control_x = -5,  
  effect_x = 5.5,  
  weight_x = 10,  
  PredInt_x = 7  
)
```

```
forest_cont(  
  dat1,  
  measure = "SMD",  
  xlab = "Standardized Mean Difference",  
  hetero_x = -9.9,  
  study_x = -7,  
  sort = "effect",  
  treatment_x = -5,  
  control_x = -3,  
  effect_x = 2.5,  
  weight_x = 4,  
  PredInt_x = 4  
)
```

```
forest_cont(  
  dat1,  
  study.col = "darkgreen",  
  CI.col = "black",  
  diamond.col = "red",  
  Pred.Inter.col = "black",  
  measure = "SMD",  
  sort = "effect",  
  xlab = "Standardized Mean Difference",  
  contour_fill = c("gray90", "gray70", "gray50", "gray30"),  
  hetero_x = -9.9,  
  study_x = -7,  
  square.size = 9,  
  treatment_x = -5,  
  control_x = -3.2,  
  text_size = 4,  
  effect_x = 2.5,  
  weight_x = 5.8,  
  PredInt_x = 3  
)
```

Description

Creates a detailed forest plot for subgroup meta-analysis, including study-level effect sizes, subgroup pooled effects, heterogeneity statistics, overall pooled effect, and prediction intervals.

Usage

```
forest_cont_subgroup(
  dat,
  m_t_col = "mean_t",
  sd_t_col = "sd_t",
  n_t_col = "n_t",
  m_c_col = "mean_c",
  sd_c_col = "sd_c",
  n_c_col = "n_c",
  subgroup_col = "subgroup",
  study_col = "Study",
  measure = "SMD",
  method = "REML",
  xlab = NULL,
  xlim = NULL,
  model = "RE",
  title = "Subgroup Forest Plot",
  diamond.col = "red",
  overall.col = "darkgreen",
  study.col = "blue",
  CI.col = "blue",
  Pred.Inter.col = "black",
  square.size = 5,
  Pred.Int.size = 1.5,
  text_size = 3.5,
  pred = TRUE,
  xpos = list(Study = NULL, MeanT = NULL, MeanC = NULL, Effect = NULL, Weight = NULL,
             PredInt = NULL, Hetero = NULL)
)
```

Arguments

<code>dat</code>	A data frame containing the study-level data. Use <code>dat1</code> included in the package for examples.
<code>m_t_col</code>	Name of the column for treatment group means.
<code>sd_t_col</code>	Name of the column for treatment group standard deviations.
<code>n_t_col</code>	Name of the column for treatment group sample sizes.
<code>m_c_col</code>	Name of the column for control group means.
<code>sd_c_col</code>	Name of the column for control group standard deviations.
<code>n_c_col</code>	Name of the column for control group sample sizes.
<code>subgroup_col</code>	Name of the column indicating subgroup membership.

<code>study_col</code>	Name of the column with study labels.
<code>measure</code>	Effect size measure: "SMD" (standardized mean difference) or "MD" (mean difference).
<code>method</code>	Method for meta-analysis: "REML" (default) or "FE".
<code>xlab</code>	Label for the x-axis.
<code>xlim</code>	Limits for the x-axis as a numeric vector of length 2.
<code>model</code>	Random-effects ("RE") or fixed-effects ("FE") model for pooled estimates.
<code>title</code>	Plot title.
<code>diamond.col</code>	Color for subgroup pooled effect diamonds.
<code>overall.col</code>	Color for the overall pooled effect diamond.
<code>study.col</code>	Color for study-level points.
<code>CI.col</code>	Color for confidence intervals of individual studies.
<code>Pred.Inter.col</code>	Color for the overall prediction interval.
<code>square.size</code>	Maximum size of study-level effect squares.
<code>Pred.Int.size</code>	Line thickness for prediction interval.
<code>text_size</code>	Base text size for annotations.
<code>pred</code>	Logical; if TRUE, display overall prediction interval.
<code>xpos</code>	numeric vector of x-axis positions for annotations

Value

A ggplot object representing the subgroup forest plot.

Examples

```
# Using the built-in dataset dat1
forest_cont_subgroup(dat1)
```

Index

* datasets

dat1, [2](#)

bcg, [2](#)

dat1, [2](#)

forest_bin, [3](#)

forest_bin_subgroup, [5](#)

forest_cont, [7](#)

forest_cont_subgroup, [10](#)